

Transponder DISC TAG

PART ID: 1063

Tiny HF RFID transponders for enclosure into virtually any form factor.

Main Specifications

LF HF UHF
Ероху
-40°C to 85°C
IP67
RoHs & Reach, CE
Small Size, Versatile, Cost- Effective, High Durability, Cryogenic resistance



Full Specifications

Product ID	1063
Material	Ероху
Shape	Potted
Short Description	Tiny HF RFID transponders for enclosure into virtually any form factor.
Long Description	Embeddable RFID transponders allow manufacturers to integrate HID Global electronic components seamlessly into tag designs optimized for any application. Small transponders are for space-constrained applications, our smallest disc-shaped units deliver high performance.
Key Features	Small Size, Versatile, Cost-Effective, High Durability, Cryogenic resistance
Main Use	Embeddable RFID
Article Type	DISC TAG
Color	Black
Thickness [mm]	1
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP67

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.



Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Embed
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1063-01-267-00	D6x1mm	HF	MB89R118	ISO/IEC 15693 & 18000-3
1063-02-269-00	D9.5x1mm	HF	Vigo	ISO 15693

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.