

Article Type	Special Form
Length [mm]	27
Width [mm]	20.5
Thickness [mm]	9
Weight [g]	5
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	90
Peak Temp I / °C	140
Peak TIME I [h]	10
Peak Temp II / °C	130
Peak TIME II [h]	100
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Cable tie
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2022-01-152-00	Yellow	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
2022-01-264-00	Yellow	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3
2022-01-349-00	Yellow	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2
2022-01-266-00	Yellow	HF	NTAG216	ISO/IEC 14443A & 18000-3
2022-02-152-00	Blue	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
2022-02-264-00	Blue	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3
2022-02-349-00	Blue	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2
2022-02-266-00	Blue	HF	NTAG216	ISO/IEC 14443A & 18000-3
2022-03-152-00	Green	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
2022-03-264-00	Green	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3
2022-03-349-00	Green	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2
2022-03-266-00	Green	HF	NTAG216	ISO/IEC 14443A & 18000-3
2022-04-152-00	Black	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
2022-04-264-00	Black	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3
2022-04-349-00	Black	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2
2022-04-266-00	Black	HF	NTAG216	ISO/IEC 14443A & 18000-3