SIGMA
SMART TAG
Sensor TAG

PART ID:
4900

These devices are very useful for wireless sensors applications in industrial solutions, for quality check in food and pharma industry, for temperature check in maintenance processes and transport and logistics. These Sensors are operating optimal with microsensys standard RFID reader.

Main Specifications

Frequencies	LF **HF** UHF
Material	Epoxy
Operating Temperature	-35°C to 105°C
IP Class	IP65
Compliance	RoHs & Reach, CE
Key Features	Small Size, Heat Tolerant, High Durability
Options	Laser Engraving, Adhesive

Full Specifications

Product ID	4900
Name	SIGMA
On Metal Use	yes
Material	Epoxy
Shape	Temperature
Long Description	These devices are very useful for wireless sensors applications in industrial solutions, for quality check in food and pharma industry, for temperature check in maintenance processes and transport and logistics. These Sensors are operating optimal with microsensys standard RFID reader.
Key Features	Small Size, Heat Tolerant, High Durability
Options	Laser Engraving, Adhesive
Main Use	Food and Pharma Industry
Article Type	Sensor TAG
Color	Black
Diameter [mm]	14
Thickness [mm]	2
Operating Temp °C (min)	-35

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10

Operating Temp °C (max)	105
Storage Temp °C (min)	-25
Storage Temp °C (max)	90
IP Class	IP65
Compliance	RoHs & Reach, CE
Battery	No
Sensors	Semiconductor Sensor, Temperature
NFC and RFID Integration	HF
Internal Flash Memory	128 bit EEPROM free memory
Manage services	Reader
Data output to cloud	No

VARIANTS

ID	Variant
4900-01-901-00	Passive Temperature Sensor

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10