



PART ID: 4902

RFID Sensors are very useful for wireless sensor applications in industrial solutions, for quality check in food and pharma industry, for temperature check in maintenance processes and transport and logistics. These devices are operating optimal with microsensys standard RFID reader.

Main Specifications

Frequencies	LF HF UHF
Material	Ероху
Operating Temperature	-35°C to 85°C
IP Class	IP65
Compliance	RoHs & Reach, CE
Key Features	Small Size, Heat Tolerant, High Durability
Options	Adhesive, Laser Engraving



Full Specifications

Product ID	4902
Name	SIGMA
Material	Ероху
Shape	Pressure
Long Description	RFID Sensors are very useful for wireless sensor applications in industrial solutions, for quality check in food and pharma industry, for temperature check in maintenance processes and transport and logistics. These devices are operating optimal with microsensys standard RFID reader.
Key Features	Small Size, Heat Tolerant, High Durability
Options	Adhesive, Laser Engraving
Main Use	Food and Pharma Industry
Article Type	Sensor TAG
Color	Black
Diameter [mm]	14
Thickness [mm]	2.5
Operating Temp °C (min)	-35
Operating Temp °C (max)	85

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS

declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.



Storage Temp °C (min)	-40
0 1 ()	125
Storage Temp °C (max)	·
IP Class	IP65
Compliance	RoHs & Reach, CE
Battery	No
AC Plugs	NULL
Sensors	Piezo-Resistive MEMS Technology Sensor, Presssure
NFC and RFID Integration	HF
Internal Flash Memory	128 bit EEPROM free memory
Manage services	Reader
Data output to cloud	No

VARIANTS

ID	Variant
4902-01-901-00	Passive Pressure Sensor

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.