TECTUS

Transponder
Laundry TAG

PART ID:
1053

Laundry TAG is constructed to go through all the procedures that happen when doing laundry such as patching, washing and water extractor.

Main Specifications

Frequencies	**LF HF** UHF
Material	Polyamid
Operating Temperature	-25°C to 90°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Heat Tolerant, Durable Housing, Robust
Options	Laser Engraving, Other Chips On Request

Full Specifications

Product ID	1053
Material	Polyamid
Shape	Overmolded
Long Description	Laundry TAG is constructed to go through all the procedures that happen when doing laundry such as patching, washing and water extractor.
Key Features	Heat Tolerant, Durable Housing, Robust
Options	Laser Engraving, Other Chips On Request
Main Use	Laundry Application
Article Type	Laundry TAG
Color	Black
Diameter [mm]	22
Thickness [mm]	3
Hole	yes
Operating Temp °C (min)	-25
Operating Temp °C (max)	90
Storage Temp °C (min)	-25
Storage Temp °C (max)	160
Peak Temp I / °C	200

IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sew-in
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1053-01-113-00	D22x3mm Hole 2mm	LF	HITAG S 2048	ISO/IEC 11784 & 11785 & 14223
1053-02-295-00	D15.5x3mm no Hole	HF	MB89R119	

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10