

Transponder ON METAL

Square TAG

PART ID:
2007

On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.

Main Specifications

| | |
|-----------------------|---|
| Frequencies | LF HF UHF |
| Material | PVC |
| Operating Temperature | -25°C to 55°C |
| IP Class | IP68 |
| Compliance | RoHs & Reach, CE |
| Key Features | ON-Metal Use, Versatile, High Durability |
| Options | Offset Print, Other Chips On Request, Inkjet Print, Adhesive, Laser Engraving |



Full Specifications

| | |
|-------------------------|---|
| Product ID | 2007 |
| On Metal Use | yes |
| Material | PVC |
| Shape | Laminated |
| Short Description | On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface. |
| Long Description | On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface. |
| Key Features | ON-Metal Use, Versatile, High Durability |
| Options | Offset Print, Other Chips On Request, Inkjet Print, Adhesive, Laser Engraving |
| Article Type | Square TAG |
| Color | White |
| Length [mm] | 65 |
| Width [mm] | 25 |
| Thickness [mm] | 3.5 |
| Operating Temp °C (min) | -25 |
| Operating Temp °C (max) | 55 |
| Storage Temp °C (min) | -25 |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-----------------------|------------------|
| Storage Temp °C (max) | 75 |
| IP Class | IP68 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Sticker |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|-------------|------|------------|--------------------------|
| 2007-01-260-00 | 65x25x3.5mm | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 2007-01-263-00 | 65x25x3.5mm | HF | NTAG213 | ISO/IEC 14443A & 18000-3 |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.