

## PART ID: 2013

TECTUS transponders endure severe conditions while protecting data integrity. These small, thin discs enable discreet placement in a broad range of applications.

## **Main Specifications**

Frequencies	LF <b>HF</b> UHF
Material	PPS with Epoxy
Operating Temperature	-40°C to 90°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Small Size, ON-Metal Use, Rough Environment, Heat Tolerant, High Durability
Options	Logo, Offset Print



ECTUS

## **Full Specifications**

Product ID	2013
On Metal Use	yes
Material	PPS with Epoxy
Shape	Potted
Long Description	TECTUS transponders endure severe conditions while protecting data integrity. These small, thin discs enable discreet placement in a broad range of applications.
Key Features	Small Size, ON-Metal Use, Rough Environment, Heat Tolerant, High Durability
Options	Logo, Offset Print
Main Use	Asset Tracking
Article Type	DISC TAG
Color	Black
Diameter [mm]	12
Thickness [mm]	2
Operating Temp °C (min)	-40
Operating Temp °C (max)	90
Storage Temp °C (min)	-40
Storage Temp °C (max)	90

\*TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

**IP** Class

IP68			

ECTUS

Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Glue
Compliance	RoHs & Reach, CE

## **VARIANTS AND ICS**

ID	Variant	Band	Туре	ISO
2013-01-260-00	D12x2mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
2013-01-269-00	D12x2mm	HF	Vigo	ISO 15693

\*TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
 of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
 Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10