

SIRIUS

RFID Antenna Industry

PART ID:
4706

The SIRIUS 4706 is a aircoil antenna with stainless steel housing and was designed to be connected with fixed reader from the MAGNUM Series for used in waste management application. System integrators remove a tooth of the comb lifter and replace it with the SIRIUS LF antenna. The antenna is placed under the BIN TAG Chipnest transponder so that a good and accurate reading accuracy of the TECTUS Bin TAG 1021 is guaranteed.

Main Specifications

Frequencies	LF HF UHF
Material	Stainless Steel + Epoxy
Operating Temperature	-20°C to 80°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	Rough Environment, ASK/FSK Modulation, Stainless Steel Housing



Full Specifications

Product ID	4706
Name	SIRIUS
Material	Stainless Steel + Epoxy
Shape	Aircoil
Long Description	The SIRIUS 4706 is a aircoil antenna with stainless steel housing and was designed to be connected with fixed reader from the MAGNUM Series for used in waste management application. System integrators remove a tooth of the comb lifter and replace it with the SIRIUS LF antenna. The antenna is placed under the BIN TAG Chipnest transponder so that a good and accurate reading accuracy of the TECTUS Bin TAG 1021 is guaranteed.
Key Features	Rough Environment, ASK/FSK Modulation, Stainless Steel Housing
Main Use	Waste Management
Article Type	Industry
Color	Steel
Length [mm]	81
Width [mm]	31

© 2025 TECTUS Technology GmbH. All rights reserved.

The content, design, and technical data of this specification are the intellectual property of TECTUS. TECTUS reserves the right to change any information or data in this document without prior notice. TECTUS declines all responsibility for the use of products with any other specifications, but the ones mentioned above. Any additional requirement for a specific customer application must be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

1/2

Thickness [mm]	37
IP Class	IP67
PCB Material	Stainless Steel
Chemical Resistance	Not Specified
Flame Resistance	
Mechanical Resistance	Not Specified
Compliance	RoHs & Reach, CE
Operating Temp °C (min)	-20
Operating Temp °C (max)	80
Storage Temp °C (min)	-20
Storage Temp °C (max)	80
Typical Reading Range	100
Operating Frequency	LF
Frequency Range	125-134 KHz
Antenna Inductance L [μ H]	190 μ H
Antenna Resistance R [Ohm]	< 5 Ohm
Connection	Open Wire
Cable Type	PUR Flex Cable
Cable Length	8 m
Mounting Method	Srews

VARIANTS

ID	Variant
4706-01-000-00	PLUG M12