

BeaCon

SMART TAG
Beacon

PART ID:
4926

That industrial adhesive beacon combines RFID and Bluetooth Low energy technology. It is designed e.g. asset or item management applications such as inventory control/management among others. Optionally a passive NFC function can be added like for secure item inventory control.

Main Specifications

| | |
|-----------------------|------------------------------|
| Frequencies | LF HF UHF |
| Material | PC |
| Operating Temperature | -30°C to 60°C |
| IP Class | IP67 |
| Compliance | RoHs & Reach, CE |
| Key Features | Eddystone, Location Accuracy |
| Options | Silk Screen, Laser Engraving |



Full Specifications

| | |
|-------------------------|--|
| Product ID | 4926 |
| Name | BeaCon |
| Material | PC |
| Shape | BLE Beacon |
| Long Description | That industrial adhesive beacon combines RFID and Bluetooth Low energy technology. It is designed e.g. asset or item management applications such as inventory control/management among others. Optionally a passive NFC function can be added like for secure item inventory control. |
| Key Features | Eddystone, Location Accuracy |
| Options | Silk Screen, Laser Engraving |
| Main Use | Asset, item management and inventory control |
| Article Type | Beacon |
| Color | Blue |
| Diameter [mm] | 45 |
| Thickness [mm] | 11 |
| Operating Temp °C (min) | -30 |
| Operating Temp °C (max) | 60 |
| Storage Temp °C (min) | -30 |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|----------------------------|--------------------------|
| Storage Temp °C (max) | 60 |
| IP Class | IP67 |
| Compliance | RoHs & Reach, CE |
| Battery | CR2032 |
| Battery Life | Up to 2 years |
| Bluetooth Type | Bluetooth Low Energy 4.2 |
| Bluetooth Sensitivity | -97dBm |
| Bluetooth Max Power Output | +5dBm |
| Sensors | Accelerometer |
| NFC and RFID Integration | YES |

VARIANTS

| | |
|----------------|-----------------------|
| ID | Variant |
| 4926-01-000-00 | 45x11mm with adhesive |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.