

Wing Keyfob

Transponder
Keyfob

PART ID:
1054

Wing Keyfob has a visible inlay look. Logo and ID numbering can also be printed on the surface of this keyfob.

Main Specifications

Frequencies	LF HF UHF
Material	PC
Operating Temperature	-25°C to 55°C
IP Class	IP66
Compliance	RoHs & Reach, CE
Key Features	Durable Housing, Cost-Effective, Versatile
Options	Laser Engraving, Pad Printing, Logo



Full Specifications

Product ID	1054
Name	Wing Keyfob
Material	PC
Shape	Ultrasonic Welded
Long Description	Wing Keyfob has a visible inlay look. Logo and ID numbering can also be printed on the surface of this keyfob.
Key Features	Durable Housing, Cost-Effective, Versatile
Options	Laser Engraving, Pad Printing, Logo
Main Use	Access Control
Article Type	Keyfob
Length [mm]	55.5
Width [mm]	31
Thickness [mm]	8
Weight [g]	8.5
Operating Temp °C (min)	-25
Operating Temp °C (max)	55
Storage Temp °C (min)	-25

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Storage Temp °C (max)	75
IP Class	IP66
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Key-Hanger
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1054-01-152-00	Blue	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1054-01-260-00	Blue	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1054-01-206-00	Blue	HF	MIFARE Classic EV1 1K	ISO/IEC 14443A & 18000-3
1054-01-349-00	Blue	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2
1054-02-152-00	Green	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1054-02-260-00	Green	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1054-02-206-00	Green	HF	MIFARE Classic EV1 1K	ISO/IEC 14443A & 18000-3
1054-02-349-00	Green	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2
1054-03-152-00	Red	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1054-03-260-00	Red	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1054-03-206-00	Red	HF	MIFARE Classic EV1 1K	ISO/IEC 14443A & 18000-3
1054-03-349-00	Red	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2