

Transponder ON METAL
PCB TAG

PART ID:
2043

Read Range Fix Reader: 68cm - (US) 902-928MHz, on metal 70cm - (EU) 865-868MHz, on metal Handheld Reader: 53cm - (US) 902-928MHz, on metal 55cm - (EU) 865-868MHz, on metal Reading range depends on the environment and the reading device

Main Specifications

Frequencies	LF HF UHF
Material	FR4
Operating Temperature	-40°C to 150°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Asset Tracking, Heat Tolerant



Full Specifications

Product ID	2043
On Metal Use	yes
Material	FR4
Shape	Potted
Long Description	Read Range Fix Reader: 68cm - (US) 902-928MHz, on metal 70cm - (EU) 865-868MHz, on metal Handheld Reader: 53cm - (US) 902-928MHz, on metal 55cm - (EU) 865-868MHz, on metal Reading range depends on the environment and the reading device
Key Features	ON-Metal Use, Asset Tracking, Heat Tolerant
Article Type	PCB TAG
Color	Black
Length [mm]	42
Width [mm]	15
Thickness [mm]	2.8
Weight [g]	3.5
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	150
Storage Temp °C (min)	-40
Storage Temp °C (max)	200
Peak Temp I / °C	280

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Peak TIME I [h]	50
Peak Temp II / °C	250
Peak TIME II [h]	150
High Temp	yes
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2043-01-349-00	42x15x2.8mm with IC bump	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.