

TITAN

RFID Reader Industry OEM Board

PART ID:
4002

LF Multifrequency 125 kHz / 134 kHz Multiprotocol FDX-B / HDX Mid Range RFID OEM Reader Board TITAN 4002 with 1 Antenna Output was developed to connect 1 external antennas from the SIRIUS series and is used by system integrators in applications like animal identification of Live Stock animals in feeding systems. System integrators supporting the waste management industry integrate the OEM RFID reader board in their systems on waste trucks together with the comb- tooth and area antennas to identify waste bins carrying a BIN TAG or PLUG TAG. LF 125 kHz / 134 kHz Mid Range OEM Reader Board TITAN 4002 supports the reading of 125 kHz FDX, 134 kHz HDX RFID TAGs.



Main Specifications

| | |
|-----------------------|--|
| Frequencies | LF HF UHF |
| Material | FR4 |
| Operating Temperature | -20°C to 65°C |
| IP Class | Not Specified |
| Compliance | RoHs & Reach, CE |
| Key Features | Command Interpreter, ASK/FSK Modulation, Automatic Read Mode, Antenna Tuning Onboard |

Full Specifications

| | |
|------------------|--|
| Product ID | 4002 |
| Name | TITAN |
| Material | FR4 |
| Shape | Mid Range |
| Long Description | LF Multifrequency 125 kHz / 134 kHz Multiprotocol FDX-B / HDX Mid Range RFID OEM Reader Board TITAN 4002 with 1 Antenna Output was developed to connect 1 external antennas from the SIRIUS series and is used by system integrators in applications like animal identification of Live Stock animals in feeding systems. System integrators supporting the waste management industry integrate the OEM RFID reader board in their systems on waste trucks together with the comb- tooth and area antennas to identify waste bins carrying a BIN TAG or PLUG TAG. LF 125 kHz / 134 kHz Mid Range OEM Reader Board TITAN 4002 supports the reading of 125 kHz FDX, 134 kHz HDX RFID TAGs. |
| Key Features | Command Interpreter, ASK/FSK Modulation, Automatic Read Mode, |

TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|----------------------------|-------------------------------------|
| | Antenna Tuning Onboard |
| Comments | Reading Distance Depends On Antenna |
| Main Use | Embedd |
| Article Type | OEM Board |
| Color | Green |
| Length [mm] | 115 |
| Width [mm] | 70 |
| Thickness [mm] | 12 |
| Weight [g] | 56 |
| IP Class | Not Specified |
| PCB Material | FR4 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Compliance | RoHs & Reach, CE |
| Read / Read Write | Read |
| Typical Reading Range | 300-500mm |
| Supported Standards / Tags | EM420x, FDX-B, HDX |
| Operating Temp °C (min) | -20 |
| Operating Temp °C (max) | 65 |
| Storage Temp °C (min) | -20 |
| Storage Temp °C (max) | 65 |
| Power Supply | 10...15V DC |
| Battery Type | none |
| Battery Capacity | none |
| Operating Frequency | LF |
| Frequency Range | 125 - 134 kHz |
| Current Consumption | 230mA |
| Power over Ethernet [PoE] | none |
| Interfaces Physical | TTL/RS232/RS485 |
| Interfaces Protocol | ASCII |
| Transfer rate [Baud] | 9600 |
| Antenna Ports | 1 |
| Antenna ext. | 1 |
| GPIO | 4 |
| Number of Input | 2 |
| Number of Output | 2 |
| Connection | Terminal Clamps |
| Status [Display,LED] | 3 |
| Customized Programming | None |
| Firmware Update User | yes |
| Integrated RFID Reader | LF |
| Development Tools | API |
| Mounting Method | Screw M4 |

VARIANTS

| ID | Variant |
|----------------|---------------|
| 4002-01-000-00 | LF Read Only |
| 4002-02-000-00 | LF Read/Write |