

SIGMA  
SMART TAG  
Dev Kit

PART ID:  
4923

Main Specifications

|                       |                                   |
|-----------------------|-----------------------------------|
| Frequencies           | LF HF UHF                         |
| Material              | Other                             |
| Operating Temperature | -20°C to 60°C                     |
| IP Class              | IP68                              |
| Compliance            | RoHs & Reach, CE                  |
| Key Features          | Eddystone, iBeacon, Cloud Managed |



Full Specifications

|                         |                                   |
|-------------------------|-----------------------------------|
| Product ID              | 4923                              |
| Name                    | SIGMA                             |
| Material                | Other                             |
| Shape                   | BLE Beacon                        |
| Key Features            | Eddystone, iBeacon, Cloud Managed |
| Article Type            | Dev Kit                           |
| Color                   | Div.                              |
| Operating Temp °C (min) | -20                               |
| Operating Temp °C (max) | 60                                |
| Storage Temp °C (min)   | -20                               |
| Storage Temp °C (max)   | 60                                |
| IP Class                | IP68                              |
| Compliance              | RoHs & Reach, CE                  |
| Battery                 | Yes                               |
| Battery Life            | ~5 Yr                             |
| AC Input                | 100-240 VAC, 50/60 Hz             |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

|                            |  |
|----------------------------|--|
| AC Plugs                   | US,EU,UK,AUS                                     |
| Bluetooth Type             | Bluetooth Low Energy 4.1                         |
| Bluetooth Sensitivity      | -97dBm   |
| Bluetooth Max Power Output | +5dBm  |
| Bluetooth Antenna          | 0dBm Single Antenna, Omni Directional            |
| Bluetooth Data Rate        | 1Mbit/s / 2Mbit/s                                |
| Bluetooth Security         | 128 bit AES                                      |
| WiFi Type                  | 802.11 b/g/n                                     |
| WiFi Security              | WPA2 Personal and Enterprise Security            |
| WiFi TX Power              | 20.5dBm @ 1DSSS and 11 CCK15.0dBm @ 54 OFDM      |
| WiFi RX Sensitivity        | -97.5dBm @ 1DSSS-88.5dBm @ 11 CCK                |
| WiFi Frequency             | 2.4 Ghz with coexistence built-in with Bluetooth |
| WiFi Antenna               | 0dBm Single Antenna, Omni Directional            |
| Sensors                    | None   |
| NFC and RFID Integration   | No   |
| Internal Flash Memory      | 55KB   |
| LED                        | Red  |
| Manage services            | Cloud  |
| Data output to cloud       | 0.1 to 1Mbit Up data                             |

## VARIANTS

| ID             | Variant              |
|----------------|----------------------|
| 4923-01-000-00 | RTLS/ Asset Tracking |