

# Transponder ON METAL Square TAG

## **PART ID:** 2007

On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.

#### **Main Specifications**

Frequencies	LF <b>HF</b> UHF
Material	PVC
Operating Temperature	-25°C to 55°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	ON-Metal Use, Versatile, High Durability
Options	Offset Print, Other Chips On Request, Inkjet Print, Adhesive, Laser Engraving



## **Full Specifications**

Product ID	2007		
On Metal Use	yes		
Material	PVC		
Shape	Laminated		
Short Description	On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.		
Long Description	On-Metal Square Tag has a hard PVC substrate topped with soft Epoxy. With adhesive, it can be attached to any metallic surface.		
Key Features	ON-Metal Use, Versatile, High Durability		
Options	Offset Print, Other Chips On Request, Inkjet Print, Adhesive, Laser Engraving		
Article Type	Square TAG		
Color	White		
Length [mm]	65		
Width [mm]	25		
Thickness [mm]	3.5		
Operating Temp °C (min)	-25		
Operating Temp °C (max)	55		
Storage Temp °C (min)	-25		

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.



Storage Temp °C (max)	75
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

### **VARIANTS AND ICS**

ID	Variant	Band	Type	ISO
2007-01-260-00	65x25x3.5mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
2007-01-263-00	65x25x3.5mm	HF	NTAG213	ISO/IEC 14443A & 18000-3

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.