

Transponder ON METAL

Ceramic TAG

PART ID:
2017

Tiny, highly durable LF, HF and UHF tags discreetly mount to or embed in tools, equipment, medical instruments and more.

Main Specifications

Frequencies	LF HF UHF
Material	Ceramic
Operating Temperature	-20°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Small Size, Rough Environment, ON-Metal Use, High Durability
Options	Pad Printing



Full Specifications

Product ID	2017
Material	Ceramic
Shape	Overmolded
Short Description	Tiny, highly durable LF, HF and UHF tags discreetly mount to or embed in tools, equipment, medical instruments and more.
Long Description	Brick Tag passive contactless transponders easily integrate into RFID applications requiring discreet placement of small, featherweight tags that deliver sustainable performance. Brick Tag Ceramic units are optimized for placement on metal assets, such as tools, weaponry and surgical instrumentation. The hard shells encasing these tiny UHF transponders shield them from exposure to autoclave sterilization and demanding industrial environments.
Key Features	Small Size, Rough Environment, ON-Metal Use, High Durability
Options	Pad Printing
Main Use	Asset Tracking
Article Type	Ceramic TAG
Color	Black
Operating Temp °C (min)	-20
Operating Temp °C (max)	85
Storage Temp °C (min)	-20

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Storage Temp °C (max)	85
Peak Temp I / °C	225
Peak TIME I [h]	700
High Temp	yes
IP Class	IP68
Chemical Resistance	Mineral oil, petroleum, salt mist, vegetable oil
Flame Resistance	Not Specified
Mechanical Resistance	MIL STD 810-G
Attachment Method	Glue
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2017-04-369-00	7.8x6.8x2.7mm	UHF	Monza R6-P	ISO 18000-6C / EPC Gen2 V3
2017-05-369-00	13.1x7.8x3.1mm	UHF	Monza R6-P	ISO 18000-6C / EPC Gen2 V3