Transponder ATEX

DISC TAG

PART ID:

3031

With a central hole, Overmolded Stick Tag can be easily fixed on non-metal objects for warehouse management, process control and asset tracking.

Main Specifications

Frequencies	LF **HF UHF**
Material	Polyamid
Operating Temperature	-40°C to 60°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Rough Environment
Options	Laser Engraving, Logo



Full Specifications

Product ID	3031
Atex	yes
Material	Polyamid
Shape	Overmolded
Short Description	With a central hole, Overmolded Stick Tag can be easily fixed on non-metal objects for warehouse management, process control and asset tracking.
Key Features	Rough Environment
Options	Laser Engraving, Logo
Comments	30mm FRAM Version 2.5mm Thickness and Hole 5.2mm, 50mm Peak Temp 160°C-50h and 220°C-30min
Article Type	DISC TAG
Color	Black
Thickness [mm]	3
Weight [g]	3
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	60
Storage Temp °C (min)	-40

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10

Storage Temp °C (max)	60
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
3031-01-260-00	D30x3mm Hole 5mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
3031-01-267-00	D30x3mm Hole 5mm	HF	MB89R118	ISO/IEC 15693 & 18000-3
3031-02-260-00	D50x3mm Hole 5.2mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
3031-02-267-00	D50x3mm Hole 5.2mm	HF	MB89R118	ISO/IEC 15693 & 18000-3

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10