

SIRIUS

RFID Antenna
Industry

PART ID:
4705

The SIRIUS 4705 is a is a combined Air/Ferrite coil Antenna with Metal Support and was designed to be connected with fixed reader from the MAGNUM Series for used in waste management application. System integrators remove a tooth of the comb lifter and replace it with the SIRIUS LF antenna. The antenna is placed under the BIN TAG Chipnest transponder so that a good and accurate reading accuracy of the TECTUS Bin TAG 1021 is guaranteed.

Main Specifications

Frequencies	LF HF UHF
Material	ABS with Epoxy
Operating Temperature	-20°C to 80°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	ASK/FSK Modulation, ON-Metal Use, Rough Environment, Stainless Steel Support



Full Specifications

Product ID	4705
Name	SIRIUS
Material	ABS with Epoxy
Shape	Aircoil, Ferrite
Long Description	The SIRIUS 4705 is a is a combined Air/Ferrite coil Antenna with Metal Support and was designed to be connected with fixed reader from the MAGNUM Series for used in waste management application. System integrators remove a tooth of the comb lifter and replace it with the SIRIUS LF antenna. The antenna is placed under the BIN TAG Chipnest transponder so that a good and accurate reading accuracy of the TECTUS Bin TAG 1021 is guaranteed.
Key Features	ASK/FSK Modulation, ON-Metal Use, Rough Environment, Stainless Steel Support
Comments	Reading Distance Depends On Reader and Transponder
Main Use	Waste Management
Article Type	Industry
Color	Black
Length [mm]	81

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Width [mm]	31
Thickness [mm]	37
Weight [g]	700
IP Class	IP67
PCB Material	ABS with Epoxy
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Compliance	RoHs & Reach, CE
Operating Temp °C (min)	-20
Operating Temp °C (max)	80
Storage Temp °C (min)	-20
Storage Temp °C (max)	80
Typical Reading Range	100
Operating Frequency	LF
Frequency Range	125-134 kHz
Antenna Inductance L [µH]	190 µH
Antenna Resistance R [Ohm]	<5 Ohm
Connection	Open Wire
Cable Type	PUR Flex Cable
Cable Length	8 m
Mounting Method	Srews

VARIANTS

ID	Variant
4705-01-000-00	Open Wire