

Transponder

DISC TAG

PART ID:

1002-01-267-00

With a central hole, Overmolded Stick Tag can be easily fixed on non-metal objects for warehouse management, process control and asset tracking.

Main Specifications

Material	Polyamid
Operating Temperature	-40°C to 90°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Rough Environment
Options	Laser Engraving



Chip Specification (Chip 267)

Chip	Fujitsu - MB89R118
Frequency	13.56 MHz (HF)
Memory	UID 8 Byte; User 2K Byte FRAM
Norm	ISO/IEC 15693 & 18000-3

Full Specifications

Product ID	1002
Material	Polyamid
Shape	Overmolded
Short Description	With a central hole, Overmolded Stick Tag can be easily fixed on non-metal objects for warehouse management, process control and asset tracking.
Key Features	Rough Environment
Options	Laser Engraving
Comments	30mm FRAM Version 2.5mm Thickness and Hole 5.2mm, 50mm Peak Temp 160°C-50h and 220°C-30min
Article Type	DISC TAG
Color	Black
Thickness [mm]	3
Weight [g]	3
Hole	yes
Operating Temp °C (min)	-40

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Operating Temp °C (max)	90
Storage Temp °C (min)	-40
Storage Temp °C (max)	120
Peak Temp I / °C	120
Peak TIME I [h]	72
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1002-01-260-00	D30x3mm Hole 5mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1002-01-349-00	D30x3mm Hole 5mm	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2
1002-01-267-00	D30x3mm Hole 5mm	HF	MB89R118	ISO/IEC 15693 & 18000-3
1002-02-260-00	D50x3mm Hole 5.2mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1002-02-267-00	D50x3mm Hole 5.2mm	HF	MB89R118	ISO/IEC 15693 & 18000-3