

Transponder ATEX

Keyfob

PART ID:
3012

Other than access control, this Keyfob can also apply for logistic management which features complete hands-free solution. This Keyfob can be delivered with personalization colorful printing upon customer's request.

Main Specifications

Frequencies	LF HF UHF
Material	PVC
Operating Temperature	-10°C to 50°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Tool Tracking, Versatile, High Durability
Options	Laser Engraving, Encoding, Logo



Full Specifications

Product ID	3012
Atex	yes
Material	PVC
Shape	Laminated
Long Description	Other than access control, this Keyfob can also apply for logistic management which features complete hands-free solution. This Keyfob can be delivered with personalization colorful printing upon customer's request.
Key Features	Tool Tracking, Versatile, High Durability
Options	Laser Engraving, Encoding, Logo
Article Type	Keyfob
Color	White
Length [mm]	54
Width [mm]	28
Thickness [mm]	1.8
Weight [g]	4
Operating Temp °C (min)	-10
Operating Temp °C (max)	50
Storage Temp °C (min)	-10

Storage Temp °C (max)	50
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Key-Hanger
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
3012-01-260-00	54x28x1.8mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3