

Transponder ATEX

DISC TAG Patch

PART ID:
3026

Disc Tag, with an adhesive backing, can be mounted on any non-metallic surface.

Main Specifications

Frequencies	LF HF UHF
Material	PVC
Operating Temperature	-25°C to 55°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, Cost-Effective, Versatile
Options	Offset Print, Silk Screen, Inkjet Print, Other Chips On Request



Full Specifications

Product ID	3026
Atex	yes
Material	PVC
Shape	Laminated
Short Description	Disc Tag, with an adhesive backing, can be mounted on any non-metallic surface.
Long Description	Disc Tag, with an adhesive backing, can be mounted on any non-metallic surface.
Key Features	Ultra Thin, Cost-Effective, Versatile
Options	Offset Print, Silk Screen, Inkjet Print, Other Chips On Request
Main Use	Asset management
Article Type	DISC TAG Patch
Color	White
Operating Temp °C (min)	-25
Operating Temp °C (max)	55
Storage Temp °C (min)	-15
Storage Temp °C (max)	60
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified

Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
3026-01-152-00	D20x1.1mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
3026-01-260-00	D20x1.1mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
3026-02-152-00	D30x1.1mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
3026-02-260-00	D30x1.1mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3