

Transponder
ISO Card

PART ID:
1055

These cards combine innovative printing and radio frequency identification (RFID) technologies with industry-leading knowledge in the production of secure identity components and solutions. Proven processes and automated manufacturing ensure efficient and cost-effective production of high quality cards. ISO cards are used in billions around the world, ranging from simple, non-technology printed loyalty cards to highly secure access control, payment or citizen ID cards. ISO 7816 Compliant

Main Specifications

Frequencies	LF HF UHF
Material	PVC+PETF
Operating Temperature	-35°C to 70°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	High Quality Card, High-Resolution Print, Cost-Effective, Heat Tolerant
Options	Laser Engraving, Logo, UID Printing, Dual Frequency On Request



Full Specifications

Product ID	1055
Material	PVC+PETF
Shape	Laminated
Long Description	These cards combine innovative printing and radio frequency identification (RFID) technologies with industry-leading knowledge in the production of secure identity components and solutions. Proven processes and automated manufacturing ensure efficient and cost-effective production of high quality cards. ISO cards are used in billions around the world, ranging from simple, non-technology printed loyalty cards to highly secure access control, payment or citizen ID cards. ISO 7816 Compliant
Key Features	High Quality Card, High-Resolution Print, Cost-Effective, Heat Tolerant
Options	Laser Engraving, Logo, UID Printing, Dual Frequency On Request
Comments	Magnet Stripes: HiCo: 2750o.e. / 4000o.e. (3600o.e.) LoCo: 300o.e. / 650o.e.
Main Use	Access Control
Article Type	ISO Card
Color	White

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Length [mm]	85.6
Width [mm]	54
Thickness [mm]	0.8
Weight [g]	6
Operating Temp °C (min)	-35
Operating Temp °C (max)	70
Storage Temp °C (min)	-40
Storage Temp °C (max)	100
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Card Holder
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1055-01-152-00	ISO Card	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1055-01-206-00	ISO Card	HF	MIFARE Classic EV1 1K	ISO/IEC 14443A & 18000-3
1055-01-260-00	ISO Card	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1055-01-349-00	ISO Card	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2