Transponder ON METAL

PART ID: 2048

UHF on-metal labels are printable, small, thin self-adhesive tags that allow discreet or overt placement on metallic objects.

Main Specifications

| Frequencies | LF HF UHF |
|--------------------------|--|
| Material | PET |
| Operating Temperature | -20°C to 70°C |
| IP Class | IP69 |
| Compliance | RoHs & Reach, CE |
| Key Features | Small Size, ON-Metal Use, Versatile, Cost-Effective |
| Options | Preprinted Artwork, Encoding |
| | |



ECTUS

Full Specifications

| Product ID | 2048 |
|-------------------------|---|
| On Metal Use | yes |
| Material | PET |
| Shape | Laminated |
| Short Description | UHF on-metal labels are printable, small, thin self-adhesive tags that allow discreet or overt placement or metallic objects. |
| Long Description | On-metal UHF inlays are a quick and easy way to tag metallic, indoor assets. The small, thin self- adhesive tags can be printed and encode in stardard UHF label printers and enhance the speed and accuracy of inventory and process management. |
| Key Features | Small Size, ON-Metal Use, Versatile, Cost-Effective |
| Options | Preprinted Artwork, Encoding |
| Main Use | Asset Tracking |
| Article Type | Label |
| Length [mm] | 107 |
| Width [mm] | 19 |
| Thickness [mm] | 1 |
| Weight [g] | 1.25 |
| Operating Temp °C (min) | -20 |

*TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

| Operating Temp °C (max) | 70 |
|-------------------------|------------------|
| Storage Temp °C (min) | -20 |
| Storage Temp °C (max) | 70 |
| IP Class | IP69 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Sticker |
| Compliance | RoHs & Reach, CE |

TECTUS

VARIANTS AND ICS

| ID | Variant | Band | Туре | ISO |
|----------------|----------------------|------|---------|----------------------------|
| 2048-01-324-00 | 107x19x1mm, adhesive | UHF | UCODE 8 | ISO 18000-6C / EPC Gen2 V2 |

*TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
 of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
 Where application information is given, it is only advisory and does not form part of the specification.