

Transponder

DISC TAG

PART ID:

1004

Button Tag has an array of small sizes for selection. It is ideal for a size-constraint object or a limited area where RFID is needed.

Main Specifications

Frequencies	LF HF UHF
Material	Polyamid
Operating Temperature	-40°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Small Size, Durable Housing, Cost-Effective
Options	Adhesive, Laser Engraving, Logo



Full Specifications

Product ID	1004
Material	Polyamid
Shape	Overmolded
Short Description	Button Tag has an array of small sizes for selection. It is ideal for a size-constraint object or a limited area where RFID is needed.
Long Description	Button Tag has an array of small sizes for selection. It is ideal for a size-constraint object or a limited area where RFID is needed.
Key Features	Small Size, Durable Housing, Cost-Effective
Options	Adhesive, Laser Engraving, Logo
Comments	D12.4 200°C-0.5h
Main Use	Asset management
Article Type	DISC TAG
Color	Black
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	90
Peak Temp I / °C	250

TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Peak TIME I [h]	2
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Glue
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1004-01-260-00	D10x1.8mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1004-02-260-00	D12.4x2mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1004-02-152-00	D12.4x2mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1004-03-260-00	D14.5x3mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1004-04-264-00	D16x1.3mm	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3