

Transponder

Button/Round TAG

PART ID:

1074-01-211-00

The TECTUS Button Tag has a small size. It is ideal for a size-constraint object or a limited area where RFID is needed. The Material PPS is heat tolerant.

Main Specifications

Material	PPS+40%GF
Operating Temperature	-25°C to 90°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Small Size, Heat Tolerant, High Durability
Options	Laser Engraving, Logo, Adhesive



Chip Specification (Chip 211)

Chip	T1 - Tag-it HF-I Plus
Frequency	13.56 MHz (HF)
Memory	UID 8 Byte; User 2048 Bit
Norm	ISO/IEC 15693 & 18000-3

Full Specifications

Product ID	1074
Material	PPS+40%GF
Shape	Overmolded
Long Description	The TECTUS Button Tag has a small size. It is ideal for a size-constraint object or a limited area where RFID is needed. The Material PPS is heat tolerant.
Key Features	Small Size, Heat Tolerant, High Durability
Options	Laser Engraving, Logo, Adhesive
Article Type	Button/Round TAG
Color	Black
Diameter [mm]	22
Thickness [mm]	3
Operating Temp °C (min)	-25
Operating Temp °C (max)	90

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Storage Temp °C (min)	-40
Storage Temp °C (max)	120
IP Class	IP68
Chemical Resistance	Typical chemicals used in laundry and dry-cleaning processes
Flame Resistance	Not Specified
Mechanical Resistance	IEC 68.2.27/ IEC 68.2.6
Attachment Method	Glue
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1074-01-211-00	D22x3mm	HF	Tag-it HF-I Plus	ISO/IEC 15693 & 18000-3