

# Transponder DISC TAG

### **PART ID:** 1035

Tiny HF RFID transponders for enclosure into virtually any form factor.

#### **Main Specifications**

Frequencies	LF <b>HF</b> UHF
Material	Ероху
Operating Temperature	-40°C to 85°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	Small Size, Ultra Thin, High Durability



# **Full Specifications**

Product ID	1035
Material	Ероху
Shape	Potted
Short Description	Tiny HF RFID transponders for enclosure into virtually any form factor.
Long Description	Embeddable RFID transponders allow manufacturers to integrate HID Global electronic components seamlessly into tag designs optimized for any application. Piccolino Tag transponders are for space-constrained applications, our smallest disc-shaped units deliver high performance and up to a 16 kbit read write memory.
Key Features	Small Size, Ultra Thin, High Durability
Main Use	Embeddable RFID
Article Type	DISC TAG
Color	Transparent
Thickness [mm]	1
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP67

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.



Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Embed
Compliance	RoHs & Reach, CE

## **VARIANTS AND ICS**

ID	Variant	Band	Туре	ISO
1035-01-260-00	D9.5x1mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1035-01-267-00	D9.5x1mm	HF	MB89R118	ISO/IEC 15693 & 18000-3
1035-02-264-00	D7.5x1mm	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.