

# Transponder ATEX

## DISC TAG

**PART ID:**  
**3027**

Tag is made by overmolded process to elevate its grade to IP68. This type of tag features its small size.

### Main Specifications

Frequencies	<b>LF HF</b> UHF
Material	Polyamid
Operating Temperature	0°C to 0°C
IP Class	
Compliance	
Key Features	ON-Metal Use, Small Size, Durable Housing, Versatile, Heat Tolerant
Options	Adhesive, Laser Engraving, Pad Printing, Other Chips On Request



### Full Specifications

Product ID	3027
Atex	yes
On Metal Use	yes
Material	Polyamid
Shape	Overmolded
Short Description	Tag is made by overmolded process to elevate its grade to IP68. This type of tag features its small size.
Long Description	Tag is made by overmolded process to elevate its grade to IP68. This type of tag features its small size.
Key Features	ON-Metal Use, Small Size, Durable Housing, Versatile, Heat Tolerant
Options	Adhesive, Laser Engraving, Pad Printing, Other Chips On Request
Main Use	Asset Tracking
Article Type	DISC TAG

### VARIANTS AND ICS

ID	Variant	Band	Type	ISO
3027-01-260-00	D10x2.6mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
3027-02-260-00	D14.5x3mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3

---

ID	Variant	Band	Type	ISO
3027-03-152-00	12.4x2mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
3027-03-260-00	12.4x2mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3

---