

Transponder


Glass TAG

PART ID:
1024-01-269-00

Embeddable RFID Glass Tags with high chemical resistance and exceptional performance

Main Specifications

| | |
|-----------------------|---|
| Material | Glass |
| Operating Temperature | -25°C to 85°C |
| IP Class | IP68 |
| Compliance | RoHs & Reach, CE |
| Key Features | Small Size, Heat Tolerant, Versatile, High Durability |



Chip Specification (Chip 269)

| | |
|-----------|------------------|
| Chip | EM Marin - Vigo |
| Frequency | 13.56 MHz (HF) |
| Memory | 1024 bit |
| Norm | ISO 15693 |

Full Specifications

| | |
|-------------------------|---|
| Product ID | 1024 |
| Material | Glass |
| Shape | Potted |
| Short Description | Embeddable RFID Glass Tags with high chemical resistance and exceptional performance |
| Long Description | Glass Tag transponders can be easily inserted or molded into a variety of materials, to enable automated asset identification and management applications using RFID. The inherent properties of glass protect embedded electronics from exposure to harsh chemicals, ensure that tag readability is unaffected by immersion in liquids, and provide excellent stability over fluctuating temperatures. |
| Key Features | Small Size, Heat Tolerant, Versatile, High Durability |
| Main Use | Embeddable RFID |
| Article Type | Glass TAG |
| Color | Transparent |
| Diameter [mm] | 2.12 |
| Length [mm] | 12 |
| Operating Temp °C (min) | -25 |
| Operating Temp °C (max) | 85 |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-----------------------|------------------|
| Storage Temp °C (min) | -40 |
| Storage Temp °C (max) | 90 |
| Peak Temp I / °C | 120 |
| Peak TIME I [h] | 100 |
| Peak Temp II / °C | 140 |
| Peak TIME II [h] | 10 |
| High Temp | yes |
| Food compatible | yes |
| IP Class | IP68 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Embed |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|--------------|------|---------------|-------------------------------|
| 1024-01-152-00 | 2.12 x 12 mm | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 1024-01-113-00 | 2.12 x 12 mm | LF | HITAG S 2048 | ISO/IEC 11784 & 11785 & 14223 |
| 1024-01-269-00 | 2.12 x 12 mm | HF | Vigo | ISO 15693 |
| 1024-01-101-00 | 2.12 x 12 mm | LF | Q5 | |
| 1024-01-153-00 | 2.12 x 12 mm | LF | EM4305 | ISO/IEC 11784/85 Compatible |