

Transponder

Label

PART ID:
1027

HF and UHF Inlays & Labels apply easily to print media, packing or non-metal assets.

Main Specifications

Frequencies	LF HF UHF
Material	Paper
Operating Temperature	-20°C to 70°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, Small Size, Cost-Effective, Versatile, High Durability
Options	Offset Print, Inkjet Print



Full Specifications

Product ID	1027
Material	Paper
Shape	Laminated
Short Description	HF and UHF Inlays & Labels apply easily to print media, packing or non-metal assets.
Long Description	HF Labels are small, thin self-adhesive tags that allow discreet or overt placement. They can be easily hidden behind a poster or display or inside a product housing or package. Alternatively, they can be imprinted with visible graphics to attract the attention of people with smartphones or RFID readers. Extremely versatile and easy to integrate, HF labels enhance promotional marketing campaigns and improve the speed and accuracy of inventory and process management
Key Features	Ultra Thin, Small Size, Cost-Effective, Versatile, High Durability
Options	Offset Print, Inkjet Print
Main Use	Asset Tracking
Article Type	Label
Color	White
Operating Temp °C (min)	-20
Operating Temp °C (max)	70
Storage Temp °C (min)	-10
Storage Temp °C (max)	40

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

IP Class	IP67
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1027-01-263-00	29mm	HF	NTAG213	ISO/IEC 14443A & 18000-3
1027-02-263-00	40mm	HF	NTAG213	ISO/IEC 14443A & 18000-3

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.