

# Transponder


## Label

PART ID:

**1057-02-266-00**

### Main Specifications

Material	Paper
Operating Temperature	-25°C to 70°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, Cost-Effective, High Durability
Options	Preprinted Artwork, Thermal Transfer, Barcode, UID Printing



### Chip Specification (Chip 266)

Chip	NXP - NTAG216
Frequency	13.56 MHz ( HF )
Memory	UID 7 Byte; User 888 Byte
Norm	ISO/IEC 14443A & 18000-3

### Full Specifications

Product ID	1057
Material	Paper
Shape	Label structure square
Key Features	Ultra Thin, Cost-Effective, High Durability
Options	Preprinted Artwork, Thermal Transfer, Barcode, UID Printing
Main Use	Tamper Proof Applications
Article Type	Label
Color	White
Operating Temp °C (min)	-25
Operating Temp °C (max)	70
Storage Temp °C (min)	-25
Storage Temp °C (max)	70
IP Class	IP67
Chemical Resistance	Not Specified

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1057-01-260-00	19x19mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1057-01-266-00	19x19mm	HF	NTAG216	ISO/IEC 14443A & 18000-3
1057-02-260-00	26.5x42mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1057-02-266-00	26.5x42mm	HF	NTAG216	ISO/IEC 14443A & 18000-3
1057-02-262-00	26.5x42mm	HF	ICODE SLIX-S	ISO/IEC 15693 & 18000-3