# Transponder Label

### PART ID: 1057-02-262-00

#### **Main Specifications**

Material	Paper		
Operating Temperature	-25°C to 70°C		
IP Class	IP67		
Compliance	RoHs & Reach, CE		
Key Features	Ultra Thin, Cost-Effective, High Durability		
Options	Preprinted Artwork, Thermal Transfer, Barcode, UID Printing		



ECTUS

#### **Chip Specification (Chip 262)**

Chip	NXP - ICODE SLIX-S
Frequency	13.56 MHz ( HF )
Memory	UID 8 Byte; User 2048 Bit
Norm	ISO/IEC 15693 & 18000-3

## **Full Specifications**

Product ID	1057		
Material	Paper		
Shape	Label structure square		
Key Features	Ultra Thin, Cost-Effective, High Durability		
Options	Preprinted Artwork, Thermal Transfer, Barcode, UID Printing		
Main Use	Tamper Proof Applications		
Article Type	Label		
Color	White		
Operating Temp °C (min)	-25		
Operating Temp °C (max)	70		
Storage Temp °C (min)	-25		
Storage Temp °C (max)	70		
IP Class	IP67		
Chemical Resistance	Not Specified		

\*TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.
1/2

Flame Resistance Not Specified Mechanical Resistance Not Specified Attachment Method Sticker Compliance RoHs & Reach, CE

ECTUS

## **VARIANTS AND ICS**

ID	Variant	Band	Туре	ISO
1057-01-260-00	19x19mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1057-01-266-00	19x19mm	HF	NTAG216	ISO/IEC 14443A & 18000-3
1057-02-260-00	26.5x42mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1057-02-266-00	26.5x42mm	HF	NTAG216	ISO/IEC 14443A & 18000-3
1057-02-262-00	26.5x42mm	HF	ICODE SLIX-S	ISO/IEC 15693 & 18000-3

\*TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
 of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
 Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10