

Transponder

DISC TAG

PART ID:
1059-01-152-00

TECTUS transponders endure severe conditions while protecting data integrity. These small, thin discs enable discreet placement in a broad range of applications.

Main Specifications

| | |
|-----------------------|--|
| Material | Epoxy |
| Operating Temperature | -40°C to 85°C |
| IP Class | IP69K |
| Compliance | RoHs & Reach, CE |
| Key Features | Small Size, Durable Housing, Heat Tolerant |



Chip Specification (Chip 152)

| | |
|-----------|-----------------------------|
| Chip | EM Marin - EM4200/Unique |
| Frequency | 125 kHz (LF) |
| Memory | UID 64 Bit; Read only |
| Norm | ISO/IEC 11784/85 Compatible |

Full Specifications

| | |
|-------------------------|---|
| Product ID | 1059 |
| Material | Epoxy |
| Shape | Overmolded |
| Long Description | TECTUS transponders endure severe conditions while protecting data integrity. These small, thin discs enable discreet placement in a broad range of applications. |
| Key Features | Small Size, Durable Housing, Heat Tolerant |
| Main Use | Commercial Laundry |
| Article Type | DISC TAG |
| Color | Black |
| Diameter [mm] | 16 |
| Thickness [mm] | 3 |
| Weight [g] | 1.1 |
| Operating Temp °C (min) | -40 |
| Operating Temp °C (max) | 85 |
| Storage Temp °C (min) | -25 |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-----------------------|------------------|
| Storage Temp °C (max) | 120 |
| Peak Temp I / °C | 120 |
| High Temp | yes |
| IP Class | IP69K |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Sew-in |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|---------|------|---------------|-----------------------------|
| 1059-01-152-00 | D16x3mm | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.