

# Transponder

## DISC TAG

PART ID:

**1065-01-206-00**

The DISC PVC fired with epoxy D16mm consists of a PVC tag with an epoxy dome and is recommended for surface mount tags where a decorative aspect is desired

### Main Specifications

Material	PVC+Epoxy
Operating Temperature	-30°C to 65°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Asset Tracking, Durable Housing, High Durability



### Chip Specification (Chip 206)

Chip	NXP - MIFARE Classic EV1 1K
Frequency	13.56 MHz ( HF )
Memory	UID 4/7 Byte; User 1K Byte
Norm	ISO/IEC 14443A & 18000-3

## Full Specifications

Product ID	1065
Material	PVC+Epoxy
Shape	Potted
Long Description	The DISC PVC fired with epoxy D16mm consists of a PVC tag with an epoxy dome and is recommended for surface mount tags where a decorative aspect is desired
Key Features	Asset Tracking, Durable Housing, High Durability
Main Use	Asset Tracking
Article Type	DISC TAG
Color	Black
Diameter [mm]	16
Thickness [mm]	1.5
Weight [g]	2
Operating Temp °C (min)	-30
Operating Temp °C (max)	65
Storage Temp °C (min)	-30

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Storage Temp °C (max)	65
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1065-01-206-00	D16mm	HF	MIFARE Classic EV1 1K	ISO/IEC 14443A & 18000-3

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.