

Transponder

ISO Card

PART ID:
1081

Main Specifications

Frequencies	LF HF UHF
Material	PVC
Operating Temperature	-35°C to 50°C
IP Class	IP68
Compliance	RoHs & REACH, FCC, CE
Key Features	Cost-Effective, Dual Frequency
Options	Preprinted Artwork, Color, Offset Print



Full Specifications

Product ID	1081
Material	PVC
Shape	Laminated
Key Features	Cost-Effective, Dual Frequency
Options	Preprinted Artwork, Color, Offset Print
Article Type	ISO Card
Color	White
Length [mm]	85.6
Width [mm]	54
Thickness [mm]	0.8
Operating Temp °C (min)	-35
Operating Temp °C (max)	50
Storage Temp °C (min)	-35
Storage Temp °C (max)	50
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Card Holder
Compliance	RoHs & REACH, FCC, CE

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1081-01-806-00	Dual Frequency w. Magnet Stripe		EM 4200, Mifare S70 EV1	
1081-02-806-00	Dual Frequency without Magnet Stripe		EM 4200, Mifare S70 EV1	