

Transponder ON METAL

Label

PART ID:

2001-01-264-00

HF smart label is ideal for easy tagging onto a metallic item to assist product authentication, tracking, or asset management.

Main Specifications

Material	PET
Operating Temperature	-25°C to 70°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, Small Size, ON-Metal Use
Options	Preprinted Artwork, Thermal Transfer, Barcode, UID Printing, Glossy Surface



Chip Specification (Chip 264)

Chip	NXP - ICODE SLIX 2
Frequency	13.56 MHz (HF)
Memory	UID 8 Byte; User 2528 Bit
Norm	ISO/IEC 15693 & 18000-3

Full Specifications

Product ID	2001
On Metal Use	yes
Material	PET
Shape	Label structure round
Long Description	HF smart label is ideal for easy tagging onto a metallic item to assist product authentication, tracking, or asset management.
Key Features	Ultra Thin, Small Size, ON-Metal Use
Options	Preprinted Artwork, Thermal Transfer, Barcode, UID Printing, Glossy Surface
Main Use	Tracking
Article Type	Label
Color	White
Diameter [mm]	29
Operating Temp °C (min)	-25

© 2025 TECTUS Technology GmbH. All rights reserved.

The content, design, and technical data of this specification are the intellectual property of TECTUS. TECTUS reserves the right to change any information or data in this document without prior notice. TECTUS declines all responsibility for the use of products with any other specifications, but the ones mentioned above. Any additional requirement for a specific customer application must be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Operating Temp °C (max)	70
Storage Temp °C (min)	-25
Storage Temp °C (max)	70
IP Class	IP67
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2001-01-263-00	D29mm	HF	NTAG213	ISO/IEC 14443A & 18000-3
2001-01-266-00	D29mm	HF	NTAG216	ISO/IEC 14443A & 18000-3
2001-01-264-00	D29mm	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3
2001-02-206-00	D25mm	HF	MIFARE Classic EV1 1K	ISO/IEC 14443A & 18000-3