

# Transponder ON METAL

Label

PART ID:  
**2001-02-206-00**

HF smart label is ideal for easy tagging onto a metallic item to assist product authentication, tracking, or asset management.

Main Specifications

Material	Paper
Operating Temperature	-25°C to 70°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, Small Size, ON-Metal Use
Options	Preprinted Artwork, Thermal Transfer, Barcode, UID Printing, Glossy Surface



Chip Specification (Chip 206)

Chip	NXP - MIFARE Classic EV1 1K
Frequency	13.56 MHz ( HF )
Memory	UID 4/7 Byte; User 1K Byte
Norm	ISO/IEC 14443A & 18000-3

Full Specifications

Product ID	2001
On Metal Use	yes
Material	Paper
Shape	Label structure round
Long Description	HF smart label is ideal for easy tagging onto a metallic item to assist product authentication, tracking, or asset management.
Key Features	Ultra Thin, Small Size, ON-Metal Use
Options	Preprinted Artwork, Thermal Transfer, Barcode, UID Printing, Glossy Surface
Main Use	Tracking
Article Type	Label
Color	White
Diameter [mm]	29
Operating Temp °C (min)	-25

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Operating Temp °C (max)	70
Storage Temp °C (min)	-25
Storage Temp °C (max)	70
IP Class	IP67
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2001-01-263-00	D29mm	HF	NTAG213	ISO/IEC 14443A & 18000-3
2001-01-266-00	D29mm	HF	NTAG216	ISO/IEC 14443A & 18000-3
2001-01-260-00	D29mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
2001-02-206-00	D25mm	HF	MIFARE Classic EV1 1K	ISO/IEC 14443A & 18000-3