

Transponder ON METAL

Label

PART ID:
2018

HF/NFC on-metal labels are printable, small, thin self-adhesive tags that allow discreet or overt placement on metallic objects.

Main Specifications

Frequencies	LF HF UHF
Material	PET
Operating Temperature	-20°C to 70°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, Small Size, ON-Metal Use, Versatile, Cost-Effective
Options	Adhesive, Offset Print, Inkjet Print, Pad Printing



Full Specifications

Product ID	2018
On Metal Use	yes
Material	PET
Shape	Laminated
Short Description	HF/NFC on-metal labels are printable, small, thin self-adhesive tags that allow discreet or overt placement on metallic objects.
Long Description	On-metal HF/NFC inlays are a quick and easy way to tag metallic, indoor assets. The small, thin self-adhesive tags can be printed and encode in standard HF label printers and provide full NFC interoperability.
Key Features	Ultra Thin, Small Size, ON-Metal Use, Versatile, Cost-Effective
Options	Adhesive, Offset Print, Inkjet Print, Pad Printing
Main Use	Asset Tracking
Article Type	Label
Color	White
Diameter [mm]	30
Weight [g]	2
Operating Temp °C (min)	-20
Operating Temp °C (max)	70

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Storage Temp °C (min)	-20
Storage Temp °C (max)	70
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2018-01-263-00	D30mm	HF	NTAG213	ISO/IEC 14443A & 18000-3