

Logistic Tag

Transponder ON METAL

Square TAG

PART ID:
2026

Durable Industrial tag for RTI (Real Time identification) combining long range UHF and enhanced NFC functions. The NFC tag can easily be read with Smartphones for IOT applications

Main Specifications

| | |
|-----------------------|---|
| Frequencies | LF HF UHF |
| Material | ABS+PC |
| Operating Temperature | -35°C to 85°C |
| IP Class | IP69K |
| Compliance | RoHs & Reach, CE |
| Key Features | Rough Environment, Dual Frequency, Versatile, High Durability |
| Options | Laser Engraving, Color |



Full Specifications

| | |
|-------------------------|---|
| Product ID | 2026 |
| Name | Logistic Tag |
| On Metal Use | yes |
| Material | ABS+PC |
| Shape | Ultrasonic Welded |
| Long Description | Durable Industrial tag for RTI (Real Time identification) combining long range UHF and enhanced NFC functions. The NFC tag can easily be read with Smartphones for IOT applications |
| Key Features | Rough Environment, Dual Frequency, Versatile, High Durability |
| Options | Laser Engraving, Color |
| Main Use | Asset Tracking |
| Article Type | Square TAG |
| Color | Blue |
| Length [mm] | 98 |
| Width [mm] | 33 |
| Thickness [mm] | 12.6 |
| Weight [g] | 19 |
| Hole | yes |
| Operating Temp °C (min) | -35 |

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-------------------------|------------------|
| Operating Temp °C (max) | 85 |
| Storage Temp °C (min) | -35 |
| Storage Temp °C (max) | 85 |
| IP Class | IP69K |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Weld |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|------------------------------|------|----------------------------|--|
| 2026-01-801-00 | 98x33x12.6mm, w/ Metal Part | | EM 4237SLIX + Monza R6P | ISO 18000-63 / EPC Gen2 V2, ISO 15693 |
| 2026-02-801-00 | 98x33x12.6mm, w/o Metal Part | | EM 4237SLIX + Monza R6P | ISO 18000-63 / EPC Gen2 V2, ISO 15693 |