Transponder ON METAL

Square TAG

PART ID:

2034-01-362-00

Robust, all-purpose RAIN® UHF Tags mount to any surface material and deliver long read ranges.

Main Specifications

Material	High-Impact Plastic
Operating Temperature	-40°C to 85°C
IP Class	IP69K
Compliance	RoHs & REACH, FCC, CE
Key Features	Rough Environment, Heat Tolerant, Versatile, High Durability
Options	Adhesive, Laser Engraving



Chip Specification (Chip 362)

Chip	Impinj - Monza 4QT
Frequency	860~960 MHz (UHF)
Memory	TID 32 Bit; EPC 128 Bit; User 512 Bit
Norm	ISO 18000-6C / EPC Gen2 V2

Full Specifications

Product ID	2034
Material	High-Impact Plastic
Shape	Ultrasonic Welded
Short Description	Robust, all-purpose RAIN® UHF Tags mount to any surface material and deliver long read ranges.
Long Description	Square UHF transponders are the most advanced general-purpose RAIN® UHF tags available. With the smallest footprint, the Mini version is ideal for tagging roll-cages, boxes, furniture or tools. Square UHF transponder is available for mounting on metal, plastic or wood using standard M5 screws, rivets, industrial adhesives or welding. The tags are lightweight, waterproof and resist high-pressure / high temperature washing conditions according to the highest standard (IP69K).
Key Features	Rough Environment, Heat Tolerant, Versatile, High Durability
Options	Adhesive, Laser Engraving
Main Use	Asset Tracking
Article Type	Square TAG
Color	Blue

® TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10

Length [mm]	97
Width [mm]	27
Thickness [mm]	10
Weight [g]	12
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP69K
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	IK 09
Attachment Method	Screw/Rivet
Compliance	RoHs & REACH, FCC, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2034-01-362-00	97x27x10mm	UHF	Monza 4QT	ISO 18000-6C / EPC Gen2 V2

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10