

# Transponder ON METAL

Label

PART ID:  
**2046-01-263-00**

HF/NFC on-metal labels are printable, small, thin self-adhesive tags that allow discreet or overt placement on metallic objects.

## Main Specifications

Material	PET
Operating Temperature	-20°C to 70°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, ON-Metal Use, Versatile, Cost-Effective



## Chip Specification (Chip 263)

Chip	NXP - NTAG213
Frequency	13.56 MHz ( HF )
Memory	UID 7 Byte; User 144 Byte
Norm	ISO/IEC 14443A & 18000-3

## Full Specifications

Product ID	2046
On Metal Use	yes
Material	PET
Shape	Laminated
Short Description	HF/NFC on-metal labels are printable, small, thin self-adhesive tags that allow discreet or overt placement on metallic objects.
Long Description	On-metal HF/NFC inlays are a quick and easy way to tag metallic, indoor assets. The small, thin self-adhesive tags can be printed and encode in standard HF label printers and provide full NFC interoperability.
Key Features	Ultra Thin, ON-Metal Use, Versatile, Cost-Effective
Main Use	Asset Tracking
Article Type	Label
Length [mm]	45
Width [mm]	45
Thickness [mm]	0.8
Weight [g]	4.5

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Operating Temp °C (min)	-20
Operating Temp °C (max)	70
Storage Temp °C (min)	-20
Storage Temp °C (max)	70
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	IEC 68.2.27/ IEC 68.2.6
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
2046-01-263-00	45x45x0.8mm, adhesive	HF	NTAG213	ISO/IEC 14443A & 18000-3

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.