

Transponder ATEX

DISC TAG

PART ID:
3000-05-349-00

The ATEX Zone 1 / 21 certified 34 mm ON METAL RFID TAG is a general purpose product and useful in multiple industrial applications to optimize object identification in asset management, machine marking, mobile maintenance and service and all kind of logistics applications. The robust housing in combination with the 4.5 mm mounting hole provides the mounting in hazardous area and perfectly in and on metal environment.

Main Specifications

| | |
|-----------------------|--|
| Material | Polyamid |
| Operating Temperature | -45°C to 60°C |
| IP Class | IP68 |
| Compliance | RoHs & Reach, CE |
| Key Features | Rough Environment, High Durability |
| Options | Adhesive, Logo, Other Chips On Request |



Chip Specification (Chip 349)

| | |
|-----------|--------------------------------------|
| Chip | Alien - Higgs 3 |
| Frequency | 869 MHz (UHF) |
| Memory | TID 64 Bit; EPC 96 Bit; User 512 Bit |
| Norm | ISO 18000-6C / EPC Gen2 V2 |

Full Specifications

| | |
|------------------|--|
| Product ID | 3000 |
| Atex | yes |
| On Metal Use | yes |
| Material | Polyamid |
| Shape | Overmolded |
| Long Description | The ATEX Zone 1 / 21 certified 34 mm ON METAL RFID TAG is a general purpose product and useful in multiple industrial applications to optimize object identification in asset management, machine marking, mobile maintenance and service and all kind of logistics applications. The robust housing in combination with the 4.5 mm mounting hole provides the mounting in hazardous area and perfectly in and on metal environment. |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-------------------------|--|
| Key Features | Rough Environment, High Durability |
| Options | Adhesive, Logo, Other Chips On Request |
| Comments | Hole 4.5 mm, Other Color on Request, Adhesive 3M4604 |
| Article Type | DISC TAG |
| Diameter [mm] | 34 |
| Thickness [mm] | 6 |
| Weight [g] | 7 |
| Hole | yes |
| Operating Temp °C (min) | -45 |
| Operating Temp °C (max) | 60 |
| Storage Temp °C (min) | -45 |
| Storage Temp °C (max) | 60 |
| IP Class | IP68 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Screw/Rivet |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|--------------|------|---------------|-----------------------------|
| 3000-01-152-00 | D34mm,yellow | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3000-01-260-00 | D34mm,yellow | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3000-01-263-00 | D34mm,yellow | HF | NTAG213 | ISO/IEC 14443A & 18000-3 |
| 3000-01-266-00 | D34mm,yellow | HF | NTAG216 | ISO/IEC 14443A & 18000-3 |
| 3000-01-362-00 | D34mm,yellow | UHF | Monza 4QT | ISO 18000-6C / EPC Gen2 V2 |
| 3000-02-152-00 | D34mm,black | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3000-02-260-00 | D34mm,black | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3000-02-263-00 | D34mm,black | HF | NTAG213 | ISO/IEC 14443A & 18000-3 |
| 3000-02-266-00 | D34mm,black | HF | NTAG216 | ISO/IEC 14443A & 18000-3 |
| 3000-02-362-00 | D34mm,black | UHF | Monza 4QT | ISO 18000-6C / EPC Gen2 V2 |
| 3000-03-152-00 | D34mm,blue | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3000-03-260-00 | D34mm,blue | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3000-03-263-00 | D34mm,blue | HF | NTAG213 | ISO/IEC 14443A & 18000-3 |
| 3000-03-266-00 | D34mm,blue | HF | NTAG216 | ISO/IEC 14443A & 18000-3 |
| 3000-03-362-00 | D34mm,blue | UHF | Monza 4QT | ISO 18000-6C / EPC Gen2 V2 |
| 3000-04-152-00 | D34mm,green | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3000-04-260-00 | D34mm,green | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3000-04-263-00 | D34mm,green | HF | NTAG213 | ISO/IEC 14443A & 18000-3 |
| 3000-04-266-00 | D34mm,green | HF | NTAG216 | ISO/IEC 14443A & 18000-3 |
| 3000-04-362-00 | D34mm,green | UHF | Monza 4QT | ISO 18000-6C / EPC Gen2 V2 |
| 3000-05-152-00 | D34mm,red | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 3000-05-260-00 | D34mm,red | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 3000-05-263-00 | D34mm,red | HF | NTAG213 | ISO/IEC 14443A & 18000-3 |

| ID | Variant | Band | Type | ISO |
|----------------|-----------|------|-----------|----------------------------|
| 3000-05-266-00 | D34mm,red | HF | NTAG216 | ISO/IEC 14443A & 18000-3 |
| 3000-05-362-00 | D34mm,red | UHF | Monza 4QT | ISO 18000-6C / EPC Gen2 V2 |

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.