

Transponder ATEX DISC TAG Patch

PART ID:

3026-01-260-00

Disc Tag, with an adhesive backing, can be mounted on any nonmetallic surface.

Main Specifications

Material	PVC
Operating Temperature	-25°C to 55°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, Cost-Effective, Versatile
Options	Offset Print, Silk Screen, Inkjet Print, Other Chips On Request



Chip Specification (Chip 260)

Chip	NXP - ICODE SLIX
Frequency	13.56 MHz (HF)
Memory	UID 8 Byte; User 1024 Bit
Norm	ISO/IEC 15693 & 18000-3

Full Specifications

Product ID	3026		
Atex	yes		
Material	PVC		
Shape	Laminated		
Short Description	Disc Tag, with an adhesive backing, can be mounted on any non-metallic surface.		
Long Description	Disc Tag, with an adhesive backing, can be mounted on any non-metallic surface.		
Key Features	Ultra Thin, Cost-Effective, Versatile		
Options	Offset Print, Silk Screen, Inkjet Print, Other Chips On Request		
Main Use	Asset management		
Article Type	DISC TAG Patch		
Color	White		
Operating Temp °C (min)	-25		
Operating Temp °C (max)	55		
Storage Temp °C (min)	-15		

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.



Storage Temp °C (max)	60
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Туре	ISO
3026-01-152-00	D20x1.1mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
3026-01-260-00	D20x1.1mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
3026-02-152-00	D30x1.1mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
3026-02-260-00	D30x1.1mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3

eTECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.