

# MultiPEN

## RFID Reader ATEX Zone 2 PEN

**PART ID:**  
**4603**

The MultiPEN is an innovative RFID/NFC handheld reader that enables UIDs of passive RFID TAGs to be read with different frequency range combinations. The MultiPEN makes it possible to transfer read UIDs via Bluetooth to a host computer (tablet, laptop or smartphone). The read UIDs can also be transferred / read into the database of the device memory and transferred to the host computer later via Bluetooth or USB connection. Since a real-time clock is integrated, date and time can be automatically assigned to the read UID. The MultiPEN makes it easier for users to work and makes RFID/NFC applications in maintenance, inventory, guard control systems and logistics processes efficient due to its simple handling. RFID/NFC TAGs that are mounted close to each other or in places that are difficult to access can be easily identified due to the small size of the MultiPEN's reading tip



### Main Specifications

|                       |   |
|-----------------------|---|
| Frequencies           | <b>LF HF UHF</b>  |
| Material              | Polyamid  |
| Operating Temperature | -20°C to 60°C   |
| IP Class              | IP54  |
| Compliance            | RoHs & Reach, CE  |
| Key Features          | HID/SPP BT Interface, Real-Time Clock, OLED Display, Vibration Feedback, Dual Frequency |

### Full Specifications

|                  |  |
|------------------|--|
| Product ID       | 4603   |
| Name             | MultiPEN   |
| Atex             | yes  |
| Material         | Polyamid   |
| Shape            | Short Range  |
| Long Description | The MultiPEN is an innovative RFID/NFC handheld reader that enables UIDs of passive RFID TAGs to be read with different frequency range combinations. The MultiPEN makes it possible to transfer read UIDs via Bluetooth to a host computer (tablet, laptop or smartphone). The read UIDs can also be transferred / read into the database of the device memory and transferred to the host computer later via Bluetooth or USB connection. Since a real-time clock is |

©TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

|                            |  |
|----------------------------|--|
|                            | integrated, date and time can be automatically assigned to the read UID. The MultiPEN makes it easier for users to work and makes RFID/NFC applications in maintenance, inventory, guard control systems and logistics processes efficient due to its simple handling. RFID/NFC TAGs that are mounted close to each other or in places that are difficult to access can be easily identified due to the small size of the MultiPEN's reading tip |
| Key Features               | HID/SPP BT Interface, Real-Time Clock, OLED Display, Vibration Feedback, Dual Frequency  |
| Comments                   | Including Case And Accessories   |
| Article Type               | PEN  |
| Color                      | Black, Yellow  |
| Length [mm]                | 190  |
| Width [mm]                 | 30   |
| Thickness [mm]             | 35   |
| Weight [g]                 | 125  |
| Anticollision              | yes  |
| IP Class                   | IP54   |
| PCB Material               | FR4  |
| Chemical Resistance        | Not Specified  |
| Flame Resistance           | Not Specified  |
| Mechanical Resistance      | Not Specified  |
| Compliance                 | RoHs & Reach, CE   |
| Read / Read Write          | Read&Write   |
| Typical Reading Range      | 1...3  |
| Supported Standards / Tags | all  |
| Operating Temp °C (min)    | -20  |
| Operating Temp °C (max)    | 60   |
| Storage Temp °C (max)      | 60   |
| Power Supply               | USB  |
| Battery Type               | Li-Ion   |
| Battery Capacity           | 2000 mAh   |
| Operating Frequency        | LF+UHF   |
| Frequency Range            | 125-135kHz, 860-920MHz   |
| Power over Ethernet [PoE]  | No   |
| Interfaces Physical        | USB/Bluetooth  |
| Interfaces Protocol        | ASCII  |
| Transfer rate [Baud]       | 9600   |
| Display Size               | 4 Row  |
| Memory Capacity            | 1000 UID   |
| Display                    | OLED   |
| Development Tools          | SDK  |
| Accessories                | yes  |

## VARIANTS

| ID | Variant |
|----|---------|
|----|---------|

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

---

| ID             | Variant           |
|----------------|-------------------|
| 4603-01-000-01 | LF/UHF Read/Write |

---