

PART ID: **4907**

RFID Sensors are very useful for wireless sensor applications in industrial solutions, for quality check in food and pharma industry, for temperature check in maintenance processes and transport and logistics. These devices are operating optimal with microsensys standard RFID reader.

Main Specifications

Frequencies	LF HF UHF
Material	Polyamid
Operating Temperature	-30°C to 85°C
IP Class	IP65
Compliance	RoHs & Reach, CE
Key Features	Rough Environment, Heat Tolerant, High Durability
Options	Adhesive, Laser Engraving, UID Printing
Options	



ECTUS

Full Specifications

Product ID	4907
Name	SIGMA
Material	Polyamid
Shape	Temperature
Long Description	RFID Sensors are very useful for wireless sensor applications in industrial solutions, for quality check in food and pharma industry, for temperature check in maintenance processes and transport and logistics. These devices are operating optimal with microsensys standard RFID reader.
Key Features	Rough Environment, Heat Tolerant, High Durability
Options	Adhesive, Laser Engraving, UID Printing
Main Use	Food and Pharma Industry
Article Type	Data Logger
Color	Black/Blue
Length [mm]	54
Width [mm]	40
Thickness [mm]	4.5

^e TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer

of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

Data output to cloud	No
Manage services	Reader
Internal Flash Memory	1 Mbit, 16 bit per sample
NFC and RFID Integration	HF
Sensors	Semiconductor Sensor, Temperature
AC Plugs	NULL
Battery	Yes
Compliance	RoHs & Reach, CE
IP Class	IP65
Storage Temp °C (max)	85
Storage Temp °C (min)	-40
Operating Temp °C (max)	85
Operating Temp °C (min)	-30

VARIANTS

ID	Variant
4907-01-901-00	Active Temperature Data Logger

*TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

ECTUS