

# Transponder

## DISC TAG

### PART ID:

**1006-04-260-00**

GF Stick Tag can be put on non-metallic surface for tracking, data recording or regular patrol purpose.

### Main Specifications

Material	GF
Operating Temperature	-40°C to 85°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	Asset Tracking, Tool Tracking
Options	Laser Engraving, Offset Print



### Chip Specification (Chip 260)

Chip	NXP - ICODE SLIX
Frequency	13.56 MHz ( HF )
Memory	UID 8 Byte; User 1024 Bit
Norm	ISO/IEC 15693 & 18000-3

### Full Specifications

Product ID	1006
Material	GF
Shape	Laminated
Short Description	GF Stick Tag can be put on non-metallic surface for tracking, data recording or regular patrol purpose.
Key Features	Asset Tracking, Tool Tracking
Options	Laser Engraving, Offset Print
Comments	Hole 3/3.2/4.3mm
Main Use	Asset Management, Process Control
Article Type	DISC TAG
Color	Black
Thickness [mm]	1.6
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-25

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

Storage Temp °C (max)	120
IP Class	IP67
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1006-02-152-00	D30x1.6mm Hole 3.2mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1006-02-260-00	D30x1.6mm Hole 3.2mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1006-03-152-00	D50x1.6mm Hole 4.3mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1006-04-260-00	D50x1.6mm Hole 3mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3