Transponder

DISC TAG Patch

PART ID:

1008-01-152-00

Disc Tag, with an adhesive backing, can be mounted on any non-metallic surface.

Main Specifications

Material	PVC
Operating Temperature	-25°C to 55°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Ultra Thin, Cost-Effective, Versatile
Options	Offset Print, Silk Screen, Inkjet Print, Laser Engraving, Other Chips On Request



Chip Specification (Chip 152)

Chip	EM Marin - EM4200/Unique
Frequency	125 kHz (LF)
Memory	UID 64 Bit; Read only
Norm	ISO/IEC 11784/85 Compatible

Full Specifications

Product ID	1008
Material	PVC
Shape	Laminated
Short Description	Disc Tag, with an adhesive backing, can be mounted on any non-metallic surface.
Long Description	Disc Tag, with an adhesive backing, can be mounted on any non-metallic surface.
Key Features	Ultra Thin, Cost-Effective, Versatile
Options	Offset Print, Silk Screen, Inkjet Print, Laser Engraving, Other Chips On Request
Main Use	Asset management
Article Type	DISC TAG Patch
Color	White
Thickness [mm]	1.1
Operating Temp °C (min)	-25
Operating Temp °C (max)	55

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10

Storage Temp °C (min)	-15
Storage Temp °C (max)	75
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Sticker
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1008-01-152-00	D20x1.1mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1008-01-260-00	D20x1.1mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1008-02-152-00	D25x1.1mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1008-02-260-00	D25x1.1mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1008-03-152-00	D30x1.1mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1008-03-260-00	D30x1.1mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1008-03-264-00	D30x1.1mm	HF	ICODE SLIX 2	ISO/IEC 15693 & 18000-3
1008-04-152-00	D50x1.1mm	LF	EM4200/Unique	ISO/IEC 11784/85 Compatible
1008-04-260-00	D50x1.1mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3

© TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use
of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.
Where application information is given, it is only advisory and does not form part of the specification.

TECTUS Technology GmbH | Lustheide 85 | D-51427 Bergisch Gladbach | Phone: +49 (0) 22 04 976 88 0 | Fax: +49 (0) 22 04 976 88 10