

Transponder


PCB TAG

PART ID:
1009-02-260-00

PCB Tag is ideal for small containers or applications that require a small RFID tag or when no sufficient room is allowed.

Main Specifications

| | |
|-----------------------|---------------------------------------|
| Material | FR4 |
| Operating Temperature | -35°C to 85°C |
| IP Class | IP65 |
| Compliance | RoHs & Reach, CE |
| Key Features | Small Size, Cost-Effective, Versatile |
| Options | Adhesive, Other Chips On Request |



Chip Specification (Chip 260)

| | |
|-----------|---------------------------|
| Chip | NXP - ICODE SLIX |
| Frequency | 13.56 MHz (HF) |
| Memory | UID 8 Byte; User 1024 Bit |
| Norm | ISO/IEC 15693 & 18000-3 |

Full Specifications

| | |
|-------------------|--|
| Product ID | 1009 |
| Material | FR4 |
| Shape | PCB |
| Short Description | PCB Tag is ideal for small containers or applications that require a small RFID tag or when no sufficient room is allowed. |
| Long Description | PCB Tag is ideal for small containers or applications that require a small RFID tag or when no sufficient room is allowed. |
| Key Features | Small Size, Cost-Effective, Versatile |
| Options | Adhesive, Other Chips On Request |
| Comments | Thickness with adhesive will be 0.7mm +/- 0.1mm |
| Main Use | Embeddable RFID |
| Article Type | PCB TAG |
| Color | Green |
| Thickness [mm] | 0.55 |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-------------------------|------------------|
| Weight [g] | 0.1 |
| Operating Temp °C (min) | -35 |
| Operating Temp °C (max) | 85 |
| Storage Temp °C (min) | -35 |
| Storage Temp °C (max) | 85 |
| IP Class | IP65 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Embed |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|-------------|------|--------------|-------------------------|
| 1009-01-260-00 | D6.75x1.0mm | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 1009-02-260-00 | D7.5x1.0mm | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 1009-03-255-00 | D9x0.55mm | HF | EM4237 | ISO/IEC 15693 & 18000-3 |
| 1009-03-264-00 | D9x0.55mm | HF | ICODE SLIX 2 | ISO/IEC 15693 & 18000-3 |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.