

# PEAKID

Transponder  
Square TAG

## PART ID:

**1017-01-349-00**

Bend-it tag is a frequency independent flexible tag and operates effectively with read range of over 10meter when attached to plastic, wood etc even over curved surface. Rugged construction for high durability. Can be attached by screws with the help of two holes. Can also be provided with Adhesive tape for easy attachment. Flexible Read/Write Range (reader dependent).

## Main Specifications

Material	TPU
Operating Temperature	-25°C to 85°C
IP Class	IP68
Compliance	RoHs & Reach, CE
Key Features	Rough Environment, Versatile, High Durability, Heat Tolerant
Options	Adhesive, Color



## Chip Specification (Chip 349)

Chip	Alien - Higgs 3
Frequency	869 MHz ( UHF )
Memory	TID 64 Bit; EPC 96 Bit; User 512 Bit
Norm	ISO 18000-6C / EPC Gen2 V2

## Full Specifications

Product ID	1017
Name	PEAKID
Material	TPU
Shape	Overmolded
Long Description	Bend-it tag is a frequency independent flexible tag and operates effectively with read range of over 10meter when attached to plastic, wood etc even over curved surface. Rugged construction for high durability. Can be attached by screws with the help of two holes. Can also be provided with Adhesive tape for easy attachment. Flexible Read/Write Range (reader dependent).
Key Features	Rough Environment, Versatile, High Durability, Heat Tolerant
Options	Adhesive, Color
Comments	Broadband Version 860-960MHz

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility.

Where application information is given, it is only advisory and does not form part of the specification.

Article Type	Square TAG
Color	Black
Length [mm]	125.5
Width [mm]	30
Thickness [mm]	3
Weight [g]	13.3
Hole	yes
Operating Temp °C (min)	-25
Operating Temp °C (max)	85
Storage Temp °C (min)	-25
Storage Temp °C (max)	85
IP Class	IP68
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

## VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1017-01-349-00	125.5x30x3mm	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2