

Wristband

Transponder Special Form

PART ID:
1018-01-802-00

The Combi Wristband Tag with multi read/write capability resembles

Main Specifications

Material	ABS/TPU
Operating Temperature	-25°C to 85°C
IP Class	IP67
Compliance	RoHs & Reach, CE
Key Features	High Durability, Rough Environment, Versatile
Options	Color



Chip Specification (Chip 802)

Chip	Alien - ICode SLIX + Higgs 3
Frequency	13.56 MHz, 860~960 MHz (HF UHF)
Memory	
Norm	ISO 18000-63 / EPC Gen2 V2, ISO 15693

Full Specifications

Product ID	1018
Name	Wristband
Material	ABS/TPU
Shape	Ultrasonic Welded
Short Description	The Combi Wristband Tag with multi read/write capability resembles
Long Description	The Combi Wristband Tag with multi read/write capability resembles Wrist watch in shape and is elegant in look. Dust & water proof. Soft and non allergic to skin.
Key Features	High Durability, Rough Environment, Versatile
Options	Color
Article Type	Special Form
Color	Blue
Length [mm]	45.1
Width [mm]	40

Thickness [mm]	12.8
Weight [g]	26
Operating Temp °C (min)	-25
Operating Temp °C (max)	85
Storage Temp °C (min)	-25
Storage Temp °C (max)	85
IP Class	IP67
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	Not Specified
Attachment Method	Strap
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1018-01-260-00	233x40x13mm	HF	ICODE SLIX	ISO/IEC 15693 & 18000-3
1018-01-349-00	233x40x13mm	UHF	Higgs 3	ISO 18000-6C / EPC Gen2 V2
1018-01-802-00	233x40x13mm		ICode SLIX + Higgs 3	ISO 18000-63 / EPC Gen2 V2, ISO 15693