

BIN TAG
Transponder
Special Form

PART ID:
1021-05-349-00

Durable DIN30745 compatible RFID Tags, built to withstand the harsh environments of Waste Management.

Main Specifications

| | |
|-----------------------|---|
| Material | Polyamid |
| Operating Temperature | -40°C to 85°C |
| IP Class | IP67 |
| Compliance | RoHs & Reach, CE |
| Key Features | Rough Environment, Versatile, High Durability, Cost-Effective |
| Options | Logo |



Chip Specification (Chip 349)

| | |
|-----------|--------------------------------------|
| Chip | Alien - Higgs 3 |
| Frequency | 869 MHz (UHF) |
| Memory | TID 64 Bit; EPC 96 Bit; User 512 Bit |
| Norm | ISO 18000-6C / EPC Gen2 V2 |

Full Specifications

| | |
|-------------------|--|
| Product ID | 1021 |
| Name | BIN TAG |
| Material | Polyamid |
| Shape | Potted |
| Short Description | Durable DIN30745 compatible RFID Tags, built to withstand the harsh environments of Waste Management. |
| Long Description | TECTUS Bin Tag passive contactless transponders are ideal for cost-effective waste management. Broadly compatible, they enable pay-as-you-throw and recycling incentive programs, while eliminating error-prone and expensive manual data collection. Each durable Bin Tag transponder offers superior resistance to water, salt mist, mineral oil and petroleum, as well as high tolerance to shock and temperature variations. Each tag installs easily into standard nests, manufactured into most waste bins according to DIN 30745. |
| Key Features | Rough Environment, Versatile, High Durability, Cost-Effective |
| Options | Logo |

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

| | |
|-------------------------|------------------|
| Article Type | Special Form |
| Diameter [mm] | 30 |
| Length [mm] | 15 |
| Weight [g] | 6.4 |
| Operating Temp °C (min) | -40 |
| Operating Temp °C (max) | 85 |
| Storage Temp °C (min) | -40 |
| Storage Temp °C (max) | 90 |
| IP Class | IP67 |
| Chemical Resistance | Not Specified |
| Flame Resistance | Not Specified |
| Mechanical Resistance | Not Specified |
| Attachment Method | Screw/Rivet |
| Compliance | RoHs & Reach, CE |

VARIANTS AND ICS

| ID | Variant | Band | Type | ISO |
|----------------|---------------------------|------|---------------|-----------------------------|
| 1021-01-152-00 | M30x15mm,black | LF | EM4200/Unique | ISO/IEC 11784/85 Compatible |
| 1021-02-153-00 | M30x15mm,yellow FDX-b BDE | LF | EM4305 | ISO/IEC 11784/85 Compatible |
| 1021-03-164-00 | M30x15mm,red HDX BDE | LF | SIC 279/7999 | ISO 11784/11785 HDX |
| 1021-04-260-00 | M30x15mm,blue | HF | ICODE SLIX | ISO/IEC 15693 & 18000-3 |
| 1021-06-366-00 | M30x15mm,green | UHF | M730 | ISO 18000-6C / EPC Gen2 V2 |