

# Transponder

## Square TAG

PART ID:

**1029-01-368-00**

Robust, all-purpose RAIN® UHF Tags mount to any surface material and deliver long read ranges.

### Main Specifications

Material	ABS+PC
Operating Temperature	-40°C to 85°C
IP Class	IP69K
Compliance	RoHs & Reach, CE
Key Features	Small Size, Rough Environment, Heat Tolerant, Versatile, High Durability
Options	Adhesive, Laser Engraving, Inkjet Print



### Chip Specification (Chip 368)

Chip	Impinj - Monza R6
Frequency	860~960 MHz ( UHF )
Memory	TID 48 Bit; EPC 96 Bit
Norm	ISO 18000-6C / EPC Gen2 V2

## Full Specifications

Product ID	1029
Material	ABS+PC
Shape	Ultrasonic Welded
Short Description	Robust, all-purpose RAIN® UHF Tags mount to any surface material and deliver long read ranges.
Long Description	Square UHF transponders are the most advanced general-purpose RAIN® UHF tags available. With the smallest footprint, the Mini version is ideal for tagging roll-cages, boxes, furniture or tools. Square UHF transponder is available for mounting on metal, plastic or wood using standard M5 screws, rivets, industrial adhesives or welding. The tags are lightweight, waterproof and resist high-pressure / high temperature washing conditions according to the highest standard (IP69K).
Key Features	Small Size, Rough Environment, Heat Tolerant, Versatile, High Durability
Options	Adhesive, Laser Engraving, Inkjet Print
Comments	Hole 4.5 mm
Main Use	Asset Tracking
Article Type	Square TAG

Color	Grey
Length [mm]	60
Width [mm]	18
Thickness [mm]	8
Weight [g]	6.3
Hole	yes
Operating Temp °C (min)	-40
Operating Temp °C (max)	85
Storage Temp °C (min)	-40
Storage Temp °C (max)	85
IP Class	IP69K
Chemical Resistance	Not Specified
Flame Resistance	Not Specified
Mechanical Resistance	IK 07
Attachment Method	Screw/Rivet
Compliance	RoHs & Reach, CE

VARIANTS AND ICS

ID	Variant	Band	Type	ISO
1029-01-368-00	60x18x8mm	UHF	Monza R6	ISO 18000-6C / EPC Gen2 V2

®TECTUS reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. TECTUS declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.